



RF24-105mm F4 L IS USM

- Lens control ring for fast intuitive shooting.
- 5 stop Image Stabilizer.
- Nano USM for movie shooting with a quiet and smooth AF.
- Uses a circular 9-blade aperture for exquisite soft-toned images.
- Air Sphere Coating (ASC) reduces ghosting.

no one sees it like you

Canon



TECHNICAL SPECIFICATIONS

RF24-105mm F4 L IS USM		
Optical Features/Specifications		
	Angle of view (horzntl, vertl, diagnl)	74°, 53°, 84°
	Lens construction (elements/groups)	18/14
	No. of diaphragm blades	9
	Minimum aperture	f/4
	Closest focussing distance (m)	0.45m
	Maximum magnification (x)	0.24x
	Distance Information	Via EVF or LCD
	Air Sphere Coating (ASC)	YES
	AF actuator	Nano USM
Physical Specifications		
	Dust/moisture resistance	Yes ¹
	Filter diameter (mm)	77mm
	Max. diameter x length (mm)	83.5mm x 107.3mm
	Weight (g)	700g
Accessories		
	Lens cap	E-77II
	Lens hood	EW-83N
	Lens case/pouch	LP1319
	Rear cap	Lens Dust Cap RF
	Magnification with Extension Tube EF12 II	Not supported
	Magnification with Extension Tube EF25 II	Not supported
	Extender Compatibility	Not supported

¹ Lenses with dust/moisture resistance are fitted with a rubber ring on the lens mount which may cause slight abrasion of the camera mount. This in no way effects either the lens or camera performance.

For more information visit
canon.com.au
canon.co.nz

no one sees it like you

Canon