



RF50mm F1.2 L USM

- Incredibly crisp portrait lens for EOS R cameras
- Highest quality images in its class with f/1.2 lens brightness
- Lens control ring for fast intuitive shooting
- Built in Digital Lens Optimizer

no one sees it like you

Canon



TECHNICAL SPECIFICATIONS

RF50mm F1.2 L USM		
Optical Features/Specifications		
	Angle of view (horzntl, vertl, diagnl)	40°, 27°, 46°
	Lens construction (elements/groups)	15/9
	No. of diaphragm blades	10
	Minimum aperture	f/1.2
	Closest focussing distance (m)	0.4m
	Maximum magnification (x)	0.19x
	Distance Information	Via EVF or LCD
	Air Sphere Coating (ASC)	YES
	AF actuator	Ring USM
Physical Specifications		
	Dust/moisture resistance	Yes ¹
	Filter diameter (mm)	77mm
	Max. diameter x length (mm)	89.8mm x 108mm
	Weight (g)	950g
Accessories		
	Lens cap	E-77II
	Lens hood	ES-83
	Lens case/pouch	LP1319
	Rear cap	Lens Dust Cap RF
	Magnification with Extension Tube EF12 II	Not supported
	Magnification with Extension Tube EF25 II	Not supported
	Extender Compatibility	Not supported

¹ Lenses with dust/moisture resistance are fitted with a rubber ring on the lens mount which may cause slight abrasion of the camera mount. This in no way effects either the lens or camera performance.

For more information visit
canon.com.au
canon.co.nz

no one sees it like you

Canon