



EF 70-200MM f/2.8L IS III USM

- Professional's choice telephoto zoom
- Fast constant f/2.8 aperture and Image Stabilizer
- New Air Sphere Coating (ASC) protects against flare, ghosting and reduced contrast

no one sees it like you

Canon



TECHNICAL SPECIFICATIONS

EF 70-200MM f/2.8L IS III USM

Optical Features/Specifications

Angle of view (horzntl, vertl, diagnl)	29°-10°, 19°30'-7°, 34°-12°
Lens construction (elements/groups)	23/19
No. of diaphragm blades	8
Minimum aperture	32
Closest focussing distance (m)	1.2
Maximum magnification (x)	0.21 (tele)
Distance Information	Yes
AF actuator	Ring USM ¹

Physical Specifications

Dust/moisture resistance	Yes ²
Filter diameter (mm)	77
Max. diameter x length (mm)	88.8 x 199
Weight (g)	1480

Accessories

Lens cap	E-77II
Lens hood	ET-87
Lens case/pouch	LZ1326
Rear cap	Lens Dust Cap E
Magnification with Extension Tube EF12 II	0.23-0.28
Magnification with Extension Tube EF25 II	0.36-0.42
Extender Compatibility	Yes

¹ Full time Manual focus

² Lenses with dust/moisture resistance are fitted with a rubber ring on the lens mount which may cause slight abrasion of the camera mount. This in no way effects either the lens or camera performance.

For more information visit
canon.com.au
canon.co.nz

no one sees it like you

Canon